GI400 LED

Baxtran

Indicator valid for legal metrology

A versatile, compact and light weight indicator. Designed to facilitate its use thanks to the function keys, suitable for industrial and commercial applications.

PCS | CHECK | RS232 | RS232 | 230 V | IP54 | IP65 | IP68 | VERIF







FEATURES:

- ABS or Stainless steel housing.
- IP54, IP65 or IP68 protection.
- Red LED display with 6 digits of 25 mm.
- Wall support included.
- Power supplies 230Vac.
- 2 output RS232 are included.
- Unique range, multi-range ou multi-interval.
- Units: kg.
- Approval 6.000 divisions OIML class III and IV.
- EC approval.

KEYBOARD FUNCTIONS:

- Back to menu / Mode, Zero / Untare, Gross / Net, Tare Weighing total / Exit, Print / Manual sending of weight / Units, Switch On / Switch Off

FUNCTIONS:

- Weight accumulation: automatic / manual
- Totalization for display
- Gross/Net
- Tare and pre tare manual
- Zero
- Piece counting function
- Checkweigher with LED signal
- Function division 1/10 verification. Display for a few seconds

PRINTING:

- Programmer of three headings
- Printer languages (spanish, french, portuguese, italian, english).

Code #	Description	Packing dimensions (mm)	Packing weight (kg)
210027	ABS LED indicator GI400 ABS with IP54 protection	370x230x125	2,3
210116	ABS LED indicator GI400 ABS with IP54 protection Excitation 12V	370x230x125	2,3
210028	ABS LED indicator GI400 with IP65 protection	370x230x125	2,3
210030	Stainless steel LED indicator GI400i with IP54 protection	370x230x125	2,3
210135	Stainless steel LED indicator GI400i with IP54 protection Excitation 12V	370x230x125	2,3
210031	Stainless steel LED indicator GI400i with IP65 protection	370x230x125	2,3
210140	Stainless steel LED indicator GI400i with IP68 protection	370x230x125	2,3

Accessories

Code #	Accessories description
220001	Internal battery (3,7 V/5,2Ah) Tecn. Ion -Lithium
220002	Output RS485
220003	Additional plate 4/20mA
220004	Additional plate 4/E E/S relés
220005	Communication board - Ethernet
220008	Additional plate memory ALIBI/DSD
220027	Communication board - Wifi (1)

* **220003**|**220004**|**220005** choose up to 2 (in case of choosing two, one of them must be Ethernet. Internal battery cannot be chosen with: **220003**|**220004**|**220005** or with input 12VDC. (1) Wifi communication board is under development (not available).