KERN FH 100 EXT

Force-measuring device with external high-resolution measuring cell for small loads



Article codes, product groups & Status information	
Model article-code	FH 100 EXT
Model-Serie	FH-S-EXT
Assortment	Sauter
Product Type	Force measurement
Product group	Digital force-measuring devices (external sensor)
Product usage type	Main article
EAN code (Model)	4045761140455
Predecessor Model	FH 100 EXT-2.019a
Successor Model	FH 100 EXT-2.024e
Planned start date	2009-1HJ
Customs tariff number	90248000
CE Label	Yes
Country of Origin	CN

Technical data - Primary	
Max. Force	100 N
Readability	0,05 N

Technical data - Construction	
Dimension housing (W×D×H)	230×66×36 mm
Material housing	Plastic
Mounting thread	External thread M6

Technical data - Display	
Display type	LCD
Display digit height	10 mm
Display reverse	Yes

Technical data - Power supply	
Power supply	Battery & Power supply
Battery type	NiMH
Operating time (Display off)	12 h
Operating time (Display on)	10 h
Mains adapter/adapter included	CH;EURO
Protection Class	No protection class
Interfaces	RS-232 standard

Technical data - Measuring system	
Units	N
Tolerance (% from Max.)	0,5%
Force direction	Compression;tension

Technical data - Functions	
Statistic-Function	Yes
Hold-Function	Yes
Peak-Function	Yes
Limit value (Min - Max)	Yes
Audible ready signal	Yes
Interface	RS-232 standard

Technical data - Environmental conditions

Maximum operating temperature	40 °C
Minimum storage temperature	40 °C

Technical data - Packing & Shipping	
Dimensions packaging (W×D×H)	325×185×165 mm
Gross weight	2,4 kg
Net weight	1,00 kg
Shipping method	Parcel service
UN number	Ni-MH (UN 3496, Packing Instruction #0, Not Restricted as per Special Provision A199)
Packaging component - by weight - cardboard	210 g
Packaging component - by weight - plastics	14 g
Packaging component - by weight - styrofoam	680 g
Delivery time	1 d

Technical data - Counting data	
Memory	Yes
Value memory - number of groups	1
Value memory - number of cells (per group)	10

Optional Services	
DAkkS calibration - push/pull	963-361
DAkkS calibration - push only	963-261
DAkkS calibration - pull only	963-161

Functions

Standard



Option

