KERN OBE 132

Elegant, dynamic and impressive - the all-round compound microscope for schools, training and laboratories



Article codes, product groups & Status information	
Model article-code	OBE 132
Model-Serie	OBE-13
Assortment	Microscopes & Optical Metrology
Segment	Microscopes
Product group	Transmitted light microscopes
Product usage type	Main article
EAN code (Model)	4045761236004
Predecessor Model	OBE 112; OBE 113
Planned start date	2020-1HJ
Customs tariff number	90118000
CE Label	Yes
Country of Origin	CN

Technical data - Primary	
Optical System	Finite
Tube	Binocular
Eyepiece	Eyepiece HWF 10x / Ø 18mm with anti-fungus, high eye point
Standard Objectives	100x;10x;40x;4x
Objective quality	Achromatic
Illumination	3W LED (transmitted light)

Technical data - Construction	
System	Upright
Tube type	Butterfly
Tube angle	30°
Tube rotation	Yes
Nosepiece positions	4
Eye distance (max)	75 mm
Eye distance (min)	48 mm
Adjustable dioptre	One-sided
Focusing mechanics	Coaxial coarse and fine drive
Fine drive minimum	0,002 mm
Table traveling distance	50 mm;70 mm
Aperture diaphragm	Yes
Condenser Type	Abbe
Condenser aperture	1,25
Condenser mounting	Fixed
Dimensions (W×D×H)	360×150×320 mm

Technical data - Power supply	
Power supply kind	Power adapter
Input Voltage	100 V - 240V AC 50/60Hz 0,3A
Protection Class	Class III - Low voltage
Cable attachment	Removable

Technical data - Environmental conditions	
Storage Temp Min	-5 °C
Stotage Temp Max	40 °C

KERN OBE 132

Elegant, dynamic and impressive - the all-round compound microscope for schools, training and laboratories

Technical data - Packing & Shipping	
Dimensions packaging (W×D×H)	437×381×276 mm
Gross weight	6 kg
Net weight	4,6 kg
Shipping method	Parcel service
Packaging component - by weight - paper	2,024 g
Packaging component - by weight - cardboard	800,492 g
Packaging component - by weight - plastics	10,12 g
Packaging component - by weight - styrofoam	200,376 g
Packaging component - by weight - foam	0 g
Delivery time	1 d

Technical data - Verification	
WEEE	Yes

Technical data - Illumination	
Illumination directions	Transmitted light
Transmitted light type	LED
Transmitted light intensity	3 W
Dimmable	Transmitted light

Functions

Standard



Option

